Gorilla

REINFORCED WATER ACTIVATED TAPE

INTERTAPE POLYMER GROUP®

TECHNICAL DATA SHEET

DESCRIPTION

Natural kraft, 3-Way reinforced, light duty, economy grade, water-activated carton sealing tape, manufactured with a starch based adhesive. Gorilla has fiberglass reinforcement in the machine direction and polyester reinforcement in the cross direction.

PRODUCT APPLICATION

Used for two strip sealing cartons top and bottom. Works well on recycled cartons, and non-unitized loads. Recommended for use on light weight to average cartons up to 20 pounds.

CONSTRUCTION (PER 3,000 SQUARE FEET):

Top Ply: 20 Lb. Natural Kraft Paper

(virgin fibers)

Bottom Ply: 23 Lb. Natural Kraft Paper

(virgin fibers)

Laminating Adhesive: High Melt Index

Polypropylene Base Blend

Remoistenable Adhesive: 14 Lb. Synthetically

Modified Starch

MD Reinforcement: (1-1-1-1) per 70mm

(1-1-1-1/1-1-1-1) per

72mm

110 Fiberglass

CD Reinforcement: (1-1-1) Fiberglass

1.08" spacing, at 44° angle

PHYSICAL PROPERTIES:

Caliper (mils): 5.3

MD Tensile (Lbs./in.): 63

CD Tensile (Lbs./in.):



3647 Cortez Road West | Bradenton, FL 34210 | USA Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832 www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 12/10/2012

